5. 6740-242-9175 Print washer, photo., max print size, 11 in. wd, lk in. long, 115 v, Sig type PH-240-A.

3416-186-4061 Lathe, eng. bench mtg., solid bed, 3/4 hp, 220 v, AC, 60 cyc, 3 ph (RS 8100-440000).

7. 3419-223-1982 Grinding and buffing machine, utility floor mtg., 5/8 in. spindle, 1/2 hp, 110-220 v. AC, 60 eye, s ph (RS 8100-334500).

3413-529-0812 Drilling machine, upright, floor mounting, 5/8 in. drill cap., 1/2 hp, 220 v, AC, 60 eye, 3 ph, 345-3205 rpm.

9. Milling machine, equivalent to Bridgeport Milling Machine Model "J", 220 v, AC, 3 ph, 60 cyc, 9" x 32" table. R-8 Spindle taper. 1 set collets 1/8 through 3/4 #1 Bridgeport 5" swivel vise. #5 Bridgeport Right Angle Attach. #2 Bridgeport Offset boring head Cross travel stop #1, #2, #3 shell mill holders R6 shank #14 Jacobs Precision Drill Chuck

We would be overly optimistic to presume that our list is at present a complete one and will be pleased to discuss substitutions with you for any items which might not now be available. We plan to submit additional requirements in summary lists as soon as these lists are established.

Items on the following pages are required by March 1, 1961 at to prepare for subsequent photographic support as required during project test and operation.

Items 1 through 5 are repeated under Processing Equipment and Items 6 through 9 under Maintenance Equipment in the equipment breakdown lists.

Yours very truly,

25X1A

25X1A

ELG: BLE: LB inc. Cet DK BLE

LEW

Equipment Component List Photographic Laboratory & Shop

25X1A.

25X1A

The following items are required by March 1, 1961. Ship and hold all A quantity of one each is desired except wherein noted following the stock identification number.

Stock No.	Description
3432-277-6577	Soldering Iron - Electric thermostatically cont 110 v AC 60 cyc w/o tips
3460-180-0840	Clamp - Parallel toolmakers 2 in.
3460-221-1104 (2)	Vise, bench and mach table, jaw, 2 in.
4240-202-5811	Faceshield, industrial, plas mask
4240-278-9646 (3)	Goggles, industrial, frame one-piece single apert, plas, clear, ventilated, w/clear plas lens, polarized, w/o carrying case (pr)
4310-371-9400	Compressor, reciprocating, power dr, air, 2 stages, 5.3 cfm piston displacement, 100 psi dischg press., mtr, 1 ph, AC, air rec tank, mtd
4930-262-8869	Oiler, hand, compressible surf. fed, 8 oz cap., 7 in. lg spout
5110-180-066 1	Shears, metal, cutting, hand, str
<i>5</i> 110-186-710 7	Chisel, cold, hand, 1/2 in.
5 110-222-4395	Cutter, glas, line cutting type, wheel type cutting end
5110-223-4971	Frame - Hacksaw 10-12 in. adj
5 110- 22 3-4972	Frame, jeweler's saw, adj, 2-1/2 in. throat d
5110-234-1927	Chisel, cold, hand, 1/4 in. wd cut
5110-241-7588	Shears, bent trimmers, 10 in. grade 2
5110-243-0884	Drill, breast, w/spirit level, 0 to 3/8 in. cap
5110-268-4224	Stripper, wire, hand, w/auto. stop, 8-22 AWG and AN cap.
5120-180-0550	Screwdriver, flat tip, wood handle, 1-1/2 in. lg blade
5120-180-0716	Screwdriver - Common w/screw holding att 1gth of blade 4 in. approx 7/32 in. wd
5120-160-0907 (4)	Clamp - C lt serv 3 in.
5120-180-0909 (4)	Clamp, C, 6 in., 2-3/4 in. d throat, It serv
5120-180-0974	Socket, socket wrench, d style, sq dr 3/8 in., 12 point, 7/16 in. size
5 120-180-0987	Socket - 12 point 3/8 in. sq dr 3/8 in. deep
5120 -1 81-6794	Socket - Universal 12 point 3/8 in. sq dr 3/8 in. BO
5120-221-7971	Wrench, torque, L handle, sq male dr, 25 in. cap.
5120-222-8852	Screwdriver, flat tip, metal handle, h in. lg blade
5120-223-6940	Extractor, screw, str fluted, w/sliding nut, 1/4 in. screw size rating, No. 1
5120-223-6941	Extractor, screw str fluted, w/sliding mut, 5/16 in. screw size rating, No. 2
5120-223-6942	Extractor, screw, str fluted, w/sliding nut, 3/8 in. screw size rating, No. 3
5120 -223-73 98	Pliers, slip joint, str nose, comb., w/cutter, 10 in.
5120-224-7271	Vise, pin, .000 to .040 in.
5120-224-9215	Universal joint, socket wrench, sq end, 3/8 in.
5120-227-6704	Socket, socket wrench, sq dr 3/8 in., 12 point, 9/16 in. size
5120-227-6705	Socket - 12 point 3/8 in. sq dr 3/4 in.
5120-227-8129	Ratchet attachment, socket wrench, reversible, so end 3/8 in.

Charlie Doc has a copy of this lesting broken down into
categories: Approved For Release 2002/10/16: CIA-RDP67B00511R000100140065/5
neld it that way

Stock No.	Description
5120-232- 5706	Socket, socket wrench, sq dr 3/8 in., 12 point, 11/16 in.
5120 -236-2139	Screwdriver - Cabinet str tip 5 in. ln blade 3/16 in. wd
5120-237-0977	tip rd blade plas handle
5120-237-0978	Socket - 12 point 3/8 in. sq dr 1/2 in.
5120-237-0979	Socket - Universal 12 point 3/8 in. sq dr 9/16 in. BO
5120-237-0980	Socket - Universal 12 point 3/8 in. sq dr 11/16 in.
51 20- 237-4969	Socket - Universal 12 point 3/6 in. sq dr 3/4 in. Bo
5120-237-4973	Handle, socket wrench, brace, 3/8 in. dr end
5120-237-4974	Sceket - 12 point 3/8 in. sq dr 5/8 in.
5120-237-6985	Socket - Universal 12 point 3/8 in. sq dr 5/8 in. BO
	Screwdriver - common lgth of blade 8 in. approx 3/8 in. wd050 in. thk
5120-240-5328	Wrench, open end, adj, single hd, & in. lg
5120-240-5330	Wrench, open end, adj, single hd, 4 in, 1g
5120-240-5364	Handle, socket wrench, ratchet, 3/8 in.
5120-240-5396	Handle - Socket wrench hinge 3/8 in. sq dr
5120-240-7308	Block, bench, mechanics, steel, 3 in. dia.
5120-241-3143	Handle, socket wrench, sliding "T", 3/8 in. dr end
5 120-241- 3185	Socket - 12 point 3/8 in. sq dr 1/2 in. deep
5120-242-3352	Socket - Universal 12 point 3/8 in. sq dr 1/2 in BO
5120-242-3354	Socket - Universal 12 point 3/8 in. sq dr 7/16 in. BO
5120-243-1348	Vise, pin., .025 to .062 in.
5120-243-1689	Extension, socket wrench, 3/8 in. sq shape end, 3 in. lg
5120-243-1690	Extension cocket around 3/8 4m as shape end, 3 in. Ig
5120-263-3458	Extension, socket wrench, 3/8 in. sq shape end, 8 in. 1g Tweezers, craftsman's, hollow jaw, 4-3/4 in.
5120-273-9203	Extension, socket wrench, 3/8 in. sq shape end, 5 in. 1g
5120-277-4063	Wrench, tap and reamer, adj, 1/16 to 1/h in.
5120-293-0045	Pliers not ning into flat dam at the action for
	Pliers, ret ring, intr, flat jaws, str tips, w/brkt, 5000 ring series, 106-175 size range
5120-293-0046	Pliers, ret ring, intr, flat jaws, str tips, w/brkt, 5000
5120-293-0048	ring series, 181-350 size range
)	Pliers, ret, ring, intr, flat jaws, str tips, w/brkt, 5000
5120-293-0049	ring series, 37-102 size range
J460-67J-0047	Pliers, ret. ring, ext, flat jaws, str tips, w/brkt, 5100 ring series, 93-143 size range
5120-293-2251	Wrench, spanner, adj, 13/32 in. thk of hook, 1-1/4 to a-1/2
, , , , , , , , , , , , , , , , , , , ,	in. dia. range, nonsparking and nonmagnetic
5120-293-3481	Pliers - Long needle nose non-side cutting 6-1/2 in. 1g
5120-299-8412	Pliers, optician's, hollow chop
51.20-534-0473	French - Spanner camera lens adj univ type D-1
5120-555-2088	Screwdriver - Common 1gth of blade 6 in approx 5/16 in wd
5120-595-9073	.046 in. thk Wrench, torque, L handle, sq male dr, 3/4 in. dr 100 to
	750 in. 1b cap.
5120-595-9526	Pliers, ret. ring ext, flat jaws, str tips, w/brkt. 5100
5130-293-1386	ring series, 0.37 to 0.87 size range
2±30 = 633 = 1300	Drill, elec, port., str dr, hvy duty, 1/4 in., 2000 rpm, AC, DC 115 v, end handle w/closed grip
5130-293-1849	Drill, elec, port., hvy duty, 1/2 in., 650 rpm, AC, DC, 115 v

- 3 -

```
Description
 Stock No.
                       Drill, twist, HSS, SS, 1/4 in.
5133-227-9658 (2)
                       Drill - Twist SS 17/64 in. HS
5133-227-9659 (2)
                       Drill - Twist SS 9/32 in. HS
5133-227-9660 (2)
                       Drill - Twist SS 11/32 in. HS
5133-227-9664 (2)
                       Drill - Twist SS 3/8 in. HS
5133-227-9666 (2)
                       Drill - Twist SS 13/32 in. HS
5133-227-9668 (2)
                       Drill - Twist SS 7/16 in. HS
5133-227-9670 (2)
                       Drill - Twist SS 1/2 in. HS
5133-227-9672 (2)
                       Drill - Twist SS 15/32 in. HS
5133-227-9673 (2)
5133-227-9692 (2)
                       Drill - Twist SS 5/16 in. HS
5133-240-8443 (2)
                       Drill, twist, HSS, SS, 19/64 in.
                       Countersink, HSS, SS, 1/h in. dia., 3/8 in., dia body,
5133-255-4061
                          82 deg. incl angle
                       Gountersink - Steel SS 3/8 in. body 1/4 in. shank
5133-255-4062
                       Tap - Hand plug 5 40
5136-199-6741 (2)
                       Tap, thd cutting, HSS, hand, plug, 10-32, NF
5136-203-6218 (2)
                       Tap, thd cutting, HSS, hand, plug, 8-32, NC
5136-203-6506 (2)
                       Tap, thd cutting, HSS, hand, plug, 10-24, NC
5136-203-6508 (2)
                       Tap, thd cutting, HSS, hand, plug, 3/8-24, NF, RH
5136-221-6106 (2)
                       Tap - Hand plug 4 48
5136-228-1004 (2)
                       Tap - Hand plug 5 44
5136-228-1005
                       Die, thd cutting, rd split, adj, 13/16 in. OD, 8-32, NC, RH Die, thd cutting, rd split, adj, 13/16 in. OD, 3-56, NF
5136-230-2778 (2)
5136-237-8263 (2)
                       Die, thd cutting, rd split, adj, 13/16 in. OD, 4-48 NF, RH
5136-239-2765 (2)
                       Die, thd cutting, rd split, adj, 13/16 in. OD, 5-lil, NF
5136-239-2766 (2)
                       Die - Round adj split 6 40 13/16 in. OD
5136-239-2767 (2)
                       Die, the cutting, rd split, adj, 13/16 in. OD, 8-36, NF, RH
5136-239-2768 (2)
                       Die, the cutting, rd split, adj, 13/16 in. OD, 10-32, NF, RH
5136-239-2769 (2)
                       Die - Round adj split 3 48 13/16 in. OD
5136-239-2774 (2)
                       Die, the cutting, rd split, 13/16 in. OD, 4-40, NC, RH
5136-239-2775 (2)
                       Die, the cutting, rd split, adj, 13/16, in. OD, 5-40, NC, RH
5136-239-2776 (2)
                       Die - Round adj split 6 32 13/16 in. OD
5136-239-2777 (2)
                       Die, thd cutting, rd split, adj, 13/16 in. OD, 10-24, NC, RH
5136-239-2779 (2)
                       Tap, thd cutting, HSS, hand, plug, 4-40, NC, RH
5136-262-3467 (2)
                       Tap, thd cutting, HSS, hand, plug, 1-64, NC, RH
5136-262-3946 (2)
                       Tap - Hand plug 1 72
5136-262-3947 (2)
                       Tap, thd cutting, HSS, hand, plug, 2-56, NC, RH size range
5136-262-3956 (2)
                       Tap, thd cutting, HSS, hand, plug, 2-64, NF, RH
5136-262-3957 (2)
                       Tap, thd cutting, HSS, hand, plug, 3-48, NC, Ed
5136-262-3958 (2)
                       Tap, the cutting, HSS, hand, plug, 3-56, NF, RH
51.36-262-3959 (2)
                       Tap, thd cutting, HSS, hand, plug, 6-40, NF
5136-516-2948 (2)
                       Tap, thd cutting, HSS, hand, plug, 8-36, NF
5136-516-2950 (2)
                       Tap, thd cutting, HSS, hand, plug, 6-32, NC
5136-516-3373 (2)
                       Tap - HSS hand bettoming 3/8 24
5136-596-4247 (2)
5136-626-6709
                       Stock - Die 13/16 in. OD die
                       Holder - Drill metal folding SS 29 drl 1/16 to 1/2 in.
5140-251-1534
                       Case, twist drill, 60 SS drl No. 1-60
5140-277-8836
                       Chest - Tool machinists 20 x 8-1/2 x 13 in.
5140-490-3835
                       Gage, twist drill and drill rod, 1-60 range
5210-221-1893
                       Gage, depth, rule, 6 in. 1g, rule grad 32nd and 64th in.
5210-221-1900
```

Stock No.	Description
5210-221-1936	Caliper, micrometer, outside, thousandths of in. units, 5-6 in. range, ratchet stop
5 21 0 - 2 23-9600	Level and plumb, wood, 18 in. 1g o/a
5210-265-7453	Tap, measuring, steel, 6 ft max. grad lgth
5210-640-0953	Indicator, dial, .025 in. range, .001 in. grad, 0-5-0 dial mks
5210-640-1160	Gage, twist drill and drill rod, 61-80 range
6230-283-9307 (4)	Light, desk, w/sw, med screw base lamp, 1 lamp, toggle sw, lamp posn adj by swivel joint, 26-3/4 in.rad, equipped w/integral securing device for horiz surf. mtg, 1 steel reflector, wired w/cable assy 6 ft 1g
6230-299-7693 (8)	Lamp Assy - Electric fluor desk adj arm clamp type 2 lamp reflector 18 in. 15 w 110 v 60 cyc
6675-526-8660	Straightedge - Steel bevel edge 18 in.
6675-526-8685	Straightedge - Steel bevel edge 12 in.
7910-254-4956(d)	Cleaner, vacuum vert. tank type w/wheels
3460-180-0837 (2)	Clamp, par, toolmaker's 3/4 in. max jaw open (RS 7900-099220)
3460-180-0839 (2)	Clamp, par toolmaker's 1-3/4 in. max jaw open (RS 7900-099300)
3460-180-0840 (2)	Clamp, par, toolmaker's, 2 in. max jaw open (RS 7900-C99320)
3460-243-1956	Dog, lathe, bent tail, 3/4 in. cap. (RS 7900-231800)
3460-243-1957	Dog, lathe, bent tail, 1 in. cap. (RS 7900-231850)
3460-243-1958	Dog, lathe, bent tail, 1-1/2 in. cap. (RS 7900-232050)
3460-517-5375	Holder, cutting tool, turning, SS, sq cutter, 1/4 in. wd (RS 7900-448290)
3460-517-5380	Holder, cutting tool, turning, offset, sq cutter 5/16 in. wd, 5/16 in. thk (RS 7900-147260)
3460-517-5384	Holder, cutting tool, thd, IH offset, shank, 3/8 in. wd, 7/8 in. h, 5 in. h (RS 7900-446800)
668 0-4 90-34 34 7CAD	Tachometer, mech, hand held, 0-1000 rpm (RS 7CAD-797309)
6760-240-7416	Meter, photo. emposure, type LM-46 (RS 6760-597-5778)
7900-073500	Caliper - Inside micrometer .200 to 1 in. grad .001
58 30-222-7 663	Intercommunication station, wire transmission, ampl not incl, incl call switch
6150-279-6342	Cable assy, power elec, 2 conduc, 16 AWG, 100 ft lg o/a, conn plug, four outlet recpt
62 30-299-7693 (3)	Light, desk, w/switch, 110 v, ac, accommodates 2 lamps
6675-183-6487	T-Square, fixed hd, 14-16 in. 1g hd, 42 in. blade
6675-245-5555	Scale, drafting, two bevel, alum. alloy, 18 in. grad 1g
6675-526-8521	Drawing board and trestle, 60 in. 1g
6675-641-3529	Drafting instrument set, set 1
7110-281-4469 (6)	Chair, rotary, steel frame, back and seat upholstered, foam rubber
7110-286-3797 (2)	Filing cabinet, cap size design, steel E finish, non- sectional type, w/o base, 5 drawers h, 1 drawer wd, o/a dim. 28 in. d, 57-1/2 in. h, 18 in. wd
7430-281-6978	Typewriter, port., upper and lower case characters, AS keyboard, no. of keys A/A, elite style
7520-224-7593	Sharpener - Pencil draftsmans single or var aperture
7520-281-5895	Stapler, paper fastening, office, desk style, designed for preformed staples, 1/2 in. crown width, 1/4 in. leg length

Stock No.	Description
7520 - 527 - 2348	Trimmer, paper, drop knife, w/guide lines parallel and at R angle to cutting edge, w/movable trimming guide, 1/2 in. spacing, bed material wood, 24 in. lg, 24 in. wd paper dim.
3920-111-7230	Truck, hand, shelf, 3 fixed steel shelves, tray type, 11 in. spacing, 4 casters, 2 swivel, 2 rigid type, solid rubber tires, steel chassis
6650-526-8247 (3)	Stereoscope, lens, pocket type, 2-1/2 power magnification
7195-691-3492	Table - Layout 4 x 8 ft x 36 in. high
3920-222-1024	Truck, hand, two-wheeled, general utility type, 52 in. lg side rails, str crossbars, 2 curved steel handles, solid rubber tires
3920-329-4283	Truck - platform hand non-tilt type wood 60 in. 1g x 36 in. wd push bar handle rubber tires 2 wheel 2 casters
3920 - 54 3- 6026	Truck, hand, lift, pallet type, 4000 lb. cap., hyd lift
4110-277-8928	Cabinet, frozen food, 18 cu. ft storage cap., w/o ice cube making equip
5110-142-4999	Saw, hand, crosscut, 24 in., 11 point
5110-595-8400	Knife, craftman's, stencil etching and cutting, remov blade
5120-187-1015	Hammer, hand, carpenter's, nailing, curved-claw, 13 oz
5120-244-9385	Puller, nail, side joint
7105-269-8463 (8)	Chair, folding, metal frame, tubr type, metal seat, metal back, medium gray color, front-to-back folding
7105-269-9275 (2)	Table, folding legs, solid top, wood, E finish, 36 in. lg, 24 in. wd
7110-267-1996 (6)	Desk, field, hinged lid, 4 plywood drawers, 1 storage compt
7125-269-8534 (2)	Cabinet, storage, steel, gray, E finish, w/lock, 18 x 78 x 36 in. o/a dim 4 adj shelves, 2 door
7520-263-3425	Perforator, paper, desk, rd perforations, w/movable paper guide, adj, 3 punches, 13/32 in.dia
7520-285-2380	Dispenser, gummed tape, lever oper type, adj or nonadjustable moisture cont, A/A lgth of tape dispensed, 8 in. max outside roll dis. 4 in. max wd tape
3432-223-2530	Soldering iron, elec, 2-1/8, 1-5/16 in. dia, 110 v, 25 w, ac
3540-234-6742	Sealer, steel strapping, hand, 5/8 in.
4310-693-2652	Compressor - Power dr type HB-9
4940-396-1664	Spray gun, paint, nonbleeder type, designed for hand oper, ext-mix type air cap., 10.68 cfm rated at 60 lb press.
	max. air consumption 1/4-18 air hose conn thd size, 3/8-18 fluid hose conn thd size NPSF
5110-142-4947	Frame, hand, hacksaw adj 8 in. to 12 in.
5120-180-0907	Clamp, C, 3 in. nom size 1 7/8 in. deep throat
5120-180-0908 (5)	Clamp, C, 4 in., 2-1/4 in. d throat, lt serv
5120-180-0909	Clamp, C, 6 in., 2-3/4 in. d throat, lt serv
5120-184-8602	Wrench, box, angular offset dbl hd, 12 point, 5/16, 3/8 in. size
5120-184-8603 5120-184-8615	Wrench, box, angular offset, dbl hd, 12 point, 3/8, 7/16 in. size Wrench, open end, fixed, single head style, nonsparking and
	non-magnetic
5120-184-8671	Wrench, box, dbl offset hd, 12 point, 5/8, 11/16 in. size
5120-184-8672	Wrench, box, dbl offset hd, 12 point, 3/4, 7/8 in. size

Stock No.	Description
5120-184-8673 5120-184-8674 5120-184-8676	Wrench, bex, dbl effset hd, 12 point, 7/8, 15/16 in. size Wrench, box, dbl offset hd, 12 point, 15/16, 1 in. size Wrench, box, angular offset dbl hd, 12 point, 1-1/4, 1-5/16 in. size
5120-184-8677 5120-184-8678 5120-204-0672	Wrench, box, dbl offset hd, 12 point, 1-1/4, 1-3/8 in. size Wrench, box, dbl offset hd, 12 point, 1-7/16, 1-1/2 in. size Screwdriver, ratchet, R angle offset, MH and LH, 3-51/64 in. lg, 2 blades
5120-223-6943 5120-245-4227	extractor, screw, str fluted, w/sliding nut, 7/16 in. screw size rating, No. 4 Vise, machinist's, swivel base, 4-1/2 in jaw, 5-1/2 in. open
5120-272-4284 5120-277-1484 (2) 5120-277-1486 (2)	Extractor, cotter pin, 6 in. Wrench, pipe, adj jaw, 8 in. lg, 1/4 to 3/4 in. Wrench, pipe, adj jaw, 14 in. lg, 1/2 to 1-1/2 in.
5120-293-0487	Hammer, hand, inserted face, 1-1/4 lb, plas, 1-1/2 in. dia.
51 20- 596 -7466 52 10-263- 03 76 62 30- 299 - 5 71 4	Etcher, elec, vibr type, ac, 60 cyc, s ph, 110 v Dividers, mech, spring type, 8 in. Flashlight, tapered tubr case, holds two 1-1/2 v bat., plas, colorless glass lens, G 3-1/2 miniature screw base lamp,
7340-162-2205	nonfocusing, 6-1/2 ft flex. exten, type A-5A Knife, pocket, w/clevis, can opener, scdr, bottle opener, 2 blades
7490-164-0541 6645-566-5537	Stencil cutting mach, hand oper, 1/2 in. character h Timer, interval, elec, 110 v, 60 cyc, ac, sync mtr, equipped with internal expiration signalling device, 60 min cap., P/N 168
6740-201-0958	Sink, photo processing temp cont, cabinet type, 72 in. 1g, 26 in. wd, 6 in. d
6740-558-5861	Tray, process. Photo. Corr. resist. steel 17-1/2 x 21-1/2 x 2-3/4 in.
6760-59 7- 5777 7310-641-6041	Densitometer, visual, transmission, 0 to 3.0 scale Hot plate, elec, 1 wire wound covered unit, 1 rotary type sw with 3 heating speeds, 115-125 v ac, 60 cyc, 1 ph, 2000 w
7520-162-6178	Sharpener, pencil, general writing point cut, w/variable aperture
6685-490-2469 8900-922000	Psychrometer, 20-120 deg. F Tank - Photographic developing 35mm film SS w/dbl reel for simultaneous development of two 5 ft lgth of 35mm film